Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2023-04-20

Section 1 - Product and Company Information

Product Name: Filler Prep

Product Part Number(s): 1060FP, 1060FP

Recommended Use: Adhesion promoter that helps filler stick to plastic.

COMPANY IDENTIFICATION: EMERGENCY TELEPHONE NUMBER:

Polyvance **24 Hour Emergency contact:** Chemtrec: 1-800-424-9300

Outside US: 703-527-3887

Rainsville, AL 35986

1128 Kirk Rd.

Information email: info@polyvance.com Customer Information Number: 256-638-4103 (7AM - 4PM (CST) M-F)

Section 2 - Hazards Identification

Appearance: Clear liquid **Odor:** Characteristic

Hazard Statement:

WARNING! Combustible liquid. May cause an allergic skin reaction.

Causes eve irritation.

Signal Word: WARNING!
Signal Word Hazard: Flammable Liquid

GHS Physical Hazard Pictogram



Flammable

GHS Health Hazard Pictogram(s)



Irritant

GHS Environmental Hazard Pictogram

Not Applicable

GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text	
Physical	H227	Combustible liquid	
Health	H317	May cause an allergic skin reaction	
Health	H320	Causes eye irritation	

Precautionary Statement:

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

GHS Precautionary Statement Codes for This Product

	•			
Statement Type	Statement Code	Statement Text		
General	P102	Keep out of reach of children		
Prevention	P261	Avoid breathing dust/fume/gas/mist/vapours/spray		
Prevention	P262	Do not get in eyes, on skin, or on clothing		

Potential Health Effects

Eye Contact: Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and

asphyxiation.

Skin Absorption: Moderate irritation, redness, blurred vision.

Inhalation: Dizziness, breathing difficulty, headaches, and loss of coordination.

Ingestion: Gastrointestinal irritation, vomiting, diarrhea.

Section 3 - Composition / Information on Ingredients

Component	CAS#	ENIECS	REACH Reg. No.	Amount
Vinyl Acetate Copolymer	24937-78-8			<3%
Heptane	142-82-5			45-50%
2-Butanone	78-93-3			<2%
Toluene	108-88-3			45-50%
Chlorinated Polyolefin	N/A			<3%

Section 4 - First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes.

Skin Contact: Flush with plenty of soap and water for 15 minutes.

Inhalation: Remove to fresh air immediately.

Ingestion: If alert, give 2-4 cupful's of milk/water. Seek medical attention immediately.

Medical Conditions

Aggravated by Exposure:

Bronchitis, CNS disorders, allergies, nausea.

Section 5 - Firefighting Measures

Extinguishing Media: Foam, CO2, Dry Chemical, Water Fog

Unusual Fire or Explosion Hazards: Handle as a flammable liquid. Vapors form an explosive mixture in air between the lower and upper explosive limits which can be ignited by many sources such as pilot lights, open flames,

electric motors and switches.

Fire Fighting Procedures:

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should

not be used except as a fog to keep nearby containers cool.

Section 6 - Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel.

Methods For Clean Up: Remove all sources of ignition. Allow volatile portion to evaporate completely. Avoid breathing

vapors and remove with inert absorbent.

Methods for Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not

Containment: contaminate lakes, streams or other water supply.

Section 7 - Handling and Storage

General Handling Practices: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid spontaneous combustion of

contaminated rags or other ignitable material. Keep out of reach of children.

Storage Requirements: Do not store near heat, sparks or flame. Store in well ventilated area. Keep closure tight and

container upright to prevent leakage. Do not puncture or incinerate. Do not sprat near fire or

open flames.

Section 8 - Precautions to Control Exposure / Personal Protection

Component	Source	Туре	Value	Remarks
2-Butanone	OSHA	PEL	300 ppm	STEL
2-Butanone	ACGIH	TLV	300 ppm	STEL
2-Butanone	ACGIH	TLV	200 ppm	TWA
2-Butanone	OSHA	PEL	200 ppm	TWA
Heptane	OSHA	PEL	500 ppm	STEL
Heptane	ACGIH	TLV	500 ppm	STEL
Heptane	ACGIH	TLV	400 ppm	TWA
Heptane	OSHA	PEL	400 ppm	TWA
Toluene	ACGIH	TLV	20 ppm	TWA
Toluene	OSHA	Ceiling	300 ppm	
Toluene	OSHA	PEL	150 ppm	STEL
Toluene	OSHA	PEL	100 ppm	TWA

Personal Protective Equipment (PPE):

Eye / Face Protection: Goggles or side-shielded safety glasses.

Skin Protection: Neoprene or butyl rubber gloves.

RespiratoryProtection: Use of a NIOSH approved chemical/mechanical filter, designed to remove a combination of

particles and vapors.

Hygenic Measures: Wash hands before eating, smoking or using the washroom.

Other Protection

Measures:

To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Wash

contaminated clothing before reuse.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure

below TLV(s)

HMIS Personal Protection: G







Section 9 - Physical and Chemical Properties

Appearance: Clear, petroleum odor

Color: Clear

Odor Threshold: Not determined

pH: Not determined

Melting Point: Not available **Freezing Point:** Not available

Boiling Point: 180

Boiling Range: Not available

Flash Point: 23F

Evaporation Rate: Not available **Flammability:** Not available

Upper Flammability Limit: 11.5

Lower Flammability Limit: 1

Vapor Pressure: Not available
Vapor Density: Heavier than air

Specific Gravity: .8

Solubility in Water: Not Soluble
Partition Coefficient: Not available
Autoignition Temperature: Not available
Decomposition Temperature: Not available

Viscosity: Not available

Section 10 - Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Excessive heat, poor ventilation, open flames, sources of sparks.

Incompatible Materials: Alkaline materials, strong acids, and oxidizing materials.

Hazardous Decomposition Carbon monoxide, carbon dioxide, various hydrocarbons, oxides of nitrogen, chlorine

Products: and possibly acrolein.

Hazardous Polymerization: Will Not Occur

Section 11 - Toxicological Information

Inhalation: Mildly toxic by inhalation.

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Disposal Method: Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do

not contaminate lakes, streams or other water supply.

ContainerDisposal: Disposal must be made according to official

regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Paint related material

Hazard Class: 3

Identification Number: UN1263

Packing Group: II

DOT Labeling: Flammable Liquid

IMDG (Maritime transport)

Proper Shipping Name: PAINT RELATED MATERIAL

UN Number: UN1263

Label: Flammable Liquid

EMS Number: F-E, S-E

Marine Polutant?: No

IATA (Air transport)

Proper Shipping Name: Paint related material

ICAO / IATA Class: 3

UN / ID Number: UN1263

Label: Flammable Liquid

Packing Group ||

Section 15 - Regulatory Information

Superfund Amendments and Reathorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986)

Sections 311 and 312

Immediate (Acute) Health Hazard: Not available
Delayed (Chronic) Health Hazard: Not available
Fire Hazard: Not available
Reactive Hazard: Not available
Sudden Realease of Pressure: Not available

(NZ) Statement: This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice

2017. HSNO Group Standard – Surface Coatings/Colourants - Flammable 002662

The following lists hazardous components and the regulatory lists for which they are required to be reported.

Component: 2-Butanone

CAS: 78-93-3 **Amount**: <2%

Component: Chlorinated Polyolefin

CAS: N/A
Amount: <3%

Component: Heptane

CAS: 142-82-5 **Amount:** 45-50%

Component: Toluene

CAS: 108-88-3 **Amount:** 45-50%

Toluene is on the California Prop 65 Reproductive list.

Toluene is listed with the Illinois toxic substances disclosure to employee act.

Toluene is listed with Massachusetts Right to Know.

Toluene is listed with Minnesota Right to Know.

Toluene is listed with New Jersey Right to Know.

Toluene is listed with Pennsylvania Right to Know.

Toluene is listed with Rhode Island Right to Know.

is listed with the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.


Component: Vinyl Acetate Copolymer

CAS: 24937-78-8 **Amount**: <3%

HMIS Rating (0 - 4)



NFPA Ratings



Section 16 - Other Information

Legend

ACGIH American Conference of Governmental Hygenists

CFR Code of Federal Regulations

DFG Deutsche Forschungsgemeinschaft

HMIS Hazardous Materials Identification System

IARC International Agency for Research on Cancer

MAK Maximum Allowable Concentration (German)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

OEL Occupational Exposure Limit

RCRA Resource Conservation and Recovery Act

STEL Short Term Exposure Limit
TLV Threshold Limit Value
TWA Time Weighted Average

DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein my be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.